



## TECHNICAL INFORMATIONS

# LIA

## 24W 4000K BRANCO

Aplique de Parede / Teto com luz direta Backlit.

Wall light / Ceiling with direct light Backlit.

Luz de Pared / Techo con luz directa Retroiluminada

**ILAR-00877**



REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	ILAR-00877	Lenght	Ø280mm	Total Luminous Flux	2040lm
Base	SMD	Width	54mm	Luminous Efficacy	110lm/W
Body Material	ABS & PC	Height	-	Beam Angle	120°
Housing Colour	White	Packaging Unit	1pc	Colour Temperature	4000K
Nominal Lifetime (EOL end of life)	30000H	Gross Weight	-	Colour Rendering Index	>80
Surface/Recessed	Surface	Volume	-		
Dimmable	NO				

  

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	24W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	24 kwh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP54	CE	YES
Operating Temperature	- 25° C to + 45° C	Protection Class	-	ROHS	YES
Starting Time 100% ON	<0.5s	Protecion Class IK (shock resistance)	-	Warranty	2 YEARS
ON/OFF Cycles	>30000				

### SIZE



Designed by Aron Light in Portugal Made in PRC

